

**Garant**
**HSS core drill N, uncoated, Ø DC h8: 22,5mm**


## Order data

Order number	116620 22,5
GTIN	4062406097189
Item class	11C

## Description

### Version:

Strong core. Sturdy jobber drill for better guidance in the hole

### Advantage:

Particularly suitable **for drilling out** holes that are out of round. Misaligned holes can be aligned.

### Recommendation:

#### Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c.$$

### Note:

#### Please note:

Do not drill the respective tapping hole Ø (see table) less than the stated size.

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**.

## Technical description

Standard	DIN 343
Number of cutting edges Z	3
Morse taper MT size	2
Feed f in steel < 750 N/mm <sup>2</sup>	0.22 mm/rev.
recommended maximum drilling depth L <sub>2</sub>	121.3 mm
Min. pre-drilling -Ø D <sub>min</sub>	16 mm
Tolerance nominal Ø	h8
Flute length L <sub>c</sub>	155 mm
Overall length L	253 mm

Nominal $\varnothing D_c$	22.5 mm
Point angle	120 degrees
Shank	Morse taper
Coating	uncoated
Tool material	HSS
Type	N
Through-coolant	no
Colour ring	without
Type of product	Jobber drill

### User data

	Suitability	$V_c$	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	45 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	40 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	30 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	25 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable only under restricted conditions	10 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable only under restricted conditions	8 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	12 m/min	M
GG(G)	suitable only under restricted conditions	25 m/min	K
wet maximum	suitable		