

# Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC m6 (mm or inch): 9/16



## **Order data**

Order number	123008 9/16		
GTIN	4062406116132		
Item class	11E		

## **Description**

#### **Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.** High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers.** Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

#### Note:

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 123010.

Form **HE:** order with **No. 123008 + 129100HE**.

Flute length  $L_c = L_2 + 1.5 \times D_c$ . Standard: Manufacturer's standard

Tolerance nominal Ø: m6 Number of cutting edges Z: 2

recommended maximum drilling depth L<sub>2</sub>: 130.7 mm

Tolerance nominal Ø: m6 Overall length L: 203 mm Shank Ø D<sub>s</sub>: 16 mm

Feed f in stainless steel > 900 N/mm<sup>2</sup>: 0.2 mm/rev.

# **Technical description**

Overall length L	203 mm
Flute length L <sub>c</sub>	152 mm
Number of cutting edges Z	2



Standard	Manufacturer's standard		
Shank tolerance	h6		
Tolerance nominal Ø	m6		
Inch nominal Ø corresponds to	14.29 mm		
Feed f in stainless steel > 900 N/mm <sup>2</sup>	0.2 mm/rev.		
recommended maximum drilling depth L <sub>2</sub>	130.7 mm		
Shank Ø D <sub>s</sub>	16 mm		
Coating	TiAlN		
Tool material	Solid carbide		
Version	8×D		
Point angle	140°		
Shank	DIN 6535 HA to h6		
Through-coolant	yes, with 25 bar		
Machining strategy	HPC		
Semi-Standard	yes		
Colour ring	blue		
Type of product	Jobber drill		

# **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Steel < 500 N/mm <sup>2</sup>	suitable	90 m/min	Р
Steel < 750 N/mm <sup>2</sup>	suitable	75 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	70 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	55 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	32 m/min	Р
INOX < 900 N/mm <sup>2</sup>	suitable	70 m/min	М
INOX > 900 N/mm <sup>2</sup>	suitable	60 m/min	М
wet maximum	suitable		
wet minimum	suitable		

## **Services**

Shank grinding Type HE 129100 HE