

Distribution block, Number of pins / Number of outlets: 5/1+3/6**Order data**

Order number	928492 5/1+3/6
GTIN	4062406117191
Item class	91P

Description**Description:****Technical data for industrial plug-in system (No. 928490; 928491; 928492):**

- Maximum connection value 230 V / AC, 16 A or 400 V / AC, 16 A.
- Maximum connected load, single-phase AC: 3.6 kW.
- Maximum connected load, three-phase AC: 10.5 kW.
- Conductor cross-section of the pre-assembled cables:
 - 3 × 1.5 mm² for single-phase AC (L, N, PE)
 - 5 × 1.5 mm² for three-phase AC (L1, L2, L3, N, PE)
- Protection class 1
- Index of Protection IP 20.

Function:

IP20: No protection against penetration by foreign bodies with $\varnothing < 12$ mm, however touching should be avoided, and no protection against water.

Note:

Initial connections and also the connection of plugs or sockets to cables should only be performed by a qualified electrician!

Technical description

Number of 3-pin outlets for No. 923420 size 3	6
Nominal voltage	400 V
Number of 5-pin outlets for No. 923419 size 5	1
Number of 5-pin outlets for No. 923420 size 5	1
Power supply	Mains operated
IP Index of Protection	IP 20
Plug type, input	GST plug-in system
Type of product	Distribution block