



## Torque screwdriver without scale, maximum torque: 34cNm



### Order data

Order number	659934 34
GTIN	4013288179395
Item class	63F

### Description

#### Version:

**Kraftform** handle for easy transmission of the required torque. With **Rapidaptor** quick-change holder for 1/4 inch bits with C 6.3 **and** E 6.3 shank.

The torque can be set using a torque analyser (No. 654300 – 654460) and a 7AF hexagon screwdriver (10AF for size 600) . **The torque screwdrivers are factory-set to the most frequently used torque setting.**

#### Function:

When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. The triggering torque is unrestricted.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Rapidaptor free-running coupling shank available from our eShop (No. 675035 size 6.3F).

### Technical description

Data can be recorded	no
Torque range	10 - 34 cNm
Weight	122 g
Adjustable trigger value	preset
Trigger principle	mechanical short-travel release

Standard	DIN EN ISO 6789
Reversible reading	cNm
Setting the trigger value	without setting scale (requires torque analyser)
set torque	0.1 Nm
Overall length L	133 mm
Torque range	0.1 - 0.34 Nm
Direction of tightening	Right-hand tightening
Torque measuring accuracy	±6 %
Measurement technology	mechanical
Bit socket	D 6,3
Bit socket	F 6.3
Release signalling	acoustic
Release signalling	haptisk
Test certificate	Manufacturer's test certificate
maximum torque	34 cNm
Connection format	Bit holder 1/4 inch
Measurement process	Torque
Feedback	triggering
Manufacturer's designation	7400 pre-set, 89 mm
Type of product	Torque screwdriver