



Torque screwdriver without scale, ESD, maximum torque: 34cNm



Order data

| | |
|--------------|---------------|
| Order number | 659954 34 |
| GTIN | 4013288179210 |
| Item class | 63F |

Description

Version:

Kraftform handle for easy transmission of the required torque. With **Rapidaptor** quick-change holder for 1/4 inch bits with C 6.3 **and** E 6.3 shank.

The torque can be set using a torque analyser (No. 654300 – 654460) and a 7AF hexagon screwdriver (10AF for size 600). **The torque screwdrivers are factory-set to the most frequently used torque setting.**

Tool handle made of conductive plastic, **suitable for ESDs.**

Function:

When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. The triggering torque is unrestricted.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Rapidaptor free-running coupling shank available from our eShop (No. 675035 size 6.3F).

Technical description

| | |
|----------------------|---------------------------------|
| maximum torque | 34 cNm |
| Torque range | 0.1 - 0.34 Nm |
| Data can be recorded | no |
| Reversible reading | cNm |
| Test certificate | Manufacturer's test certificate |

| | |
|------------------------------|---|
| Release signalling | acoustic |
| Release signalling | haptisk |
| Measurement process | Torque |
| Connection format | Bit holder 1/4 inch |
| Direction of tightening | Right-hand tightening |
| Torque range | 10 - 34 cNm |
| Measurement technology | mechanical |
| Weight | 122 g |
| Setting the trigger value | without setting scale (requires torque analyser) |
| Feedback | triggering |
| Overall length L | 133 mm |
| set torque | 0.1 Nm |
| Trigger principle | mechanical short-travel release |
| Standard | DIN EN ISO 6789 |
| Torque measuring accuracy | ±6 % |
| Adjustable trigger value | preset |
| Bit socket | D 6,3 |
| Bit socket | F 6.3 |
| Manufacturer's designation | 7400 ESD pre-set, 89 mm |
| electrostatic characteristic | EGB/ESD |
| Torque fixed setting | no |
| Type of product | Torque screwdriver |