



## Pull stud Mazak, form A, with bore, suitable for steep tapers: 40M7



### Order data

Order number	308670 40M7
GTIN	4062406120450
Item class	32Z

### Description

#### Version:

- **End face turned flat.**

Sealed.

#### Description:

The toolholder is securely pulled into the spindle by the spindle's clamping gripper using the pull stud. Pull studs come in different versions. They are an important link between the machine and tool. Stringent requirements apply for the accuracy, strength and reliability of pull studs.

#### Application:

- **For tools with taper shanks see also DIN 69871 and JIS B 6339 (MAS-BT).**
- **In machining centres (machines with automatic tool changers).**
- **In NC machines (machines without automatic tool changers).**

#### Note:

When installing the pull stud, cheque the correct tightening torque. No suitable chuck key available.

### Technical description

Overall length L	41.25 mm
suitable for steep tapers	40
Bore $\varnothing$	7 mm
maximum tightening torque	50 Nm

L <sub>1</sub>	16.25 mm
suitable for taper arbors with colour code	SK 40
Head Ø D <sub>1</sub>	18.79 mm
Thread M	M16
Collar Ø D	21.8 mm
Width across flats	19 mm
Hole characteristics	with bore
Pull stud standard	CAT
Type of product	Pull Stud