

## Garant

### GARANT Master Alu SlotMachine solid carbide roughing end mill HPC, DLC, Ø e8 DC: 12mm



#### Order data

Order number	205250 12
GTIN	4062406122249
Item class	11X

#### Description

##### Version:

For roughing.  
Special profile for machining non-ferrous metals.

##### Advantage:

**Optimised flute form, eccentric relief ground, generous chip spaces.**

Up to  $2 \times D$  into solid material at very high feed rates and smooth cutting action.

Ramping capability up to  $45^\circ$ .

Very high feed rates when plunging vertically, thanks to **special plunging geometry**.

#### Technical description

Flute length $L_c$	26 mm
Shank $\varnothing D_s$	12 mm
Cutting edge $\varnothing D_c$	12 mm
Balance quality with shank	G 2.5 with HA
Overall length L	83 mm
Feed $f_z$ for side milling in short-chipping aluminium	0.18 mm
Helix angle	35 degrees
No. of teeth Z	3
Tolerance nominal $\varnothing$	e8

Feed $f_z$ for slot milling in short-chipping aluminium	0.15 mm
Recess $\varnothing D_1$	11 mm
Shank	DIN 6535 HA to h6
Overhang length $L_1$ incl. recess	36 mm
Direction of infeed	horizontal, oblique and vertical
Corner rounding $r_v$	0.32 mm
Series	Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	0.4×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End / face mill

## User data

	Suitability	$V_c$	ISO code
Aluminium	Suitable	450 m/min	N
Aluminium (short chipping)	suitable	400 m/min	N
Alu > 10% Si	suitable	380 m/min	N
PA 66	suitable only under restricted conditions	120 m/min	N
PEEK	suitable only under restricted conditions	100 m/min	N

Cu	Suitable	160 m/min	N
CuZn	Suitable	200 m/min	N
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable only under restricted conditions		
Air	suitable		

**Services**

Shank grinding Type HB	129100 HB
------------------------	-----------