## Garant

# GARANT Master Alu SlotMachine solid carbide roughing end mill HPC, DLC, Ø e8 DC: 14mm



#### Order data

Order number	205250 14
GTIN	4062406122256
Item class	11X

#### Description

**Version:** For roughing. Special profile for machining non-ferrous metals.

#### Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Up to 2  $\times$  D into solid material at very high feed rates and smooth cutting action. Ramping capability up to 45°.

Very high feed rates when plunging vertically, thanks to **special plunging geometry**.

#### **Technical description**

Cutting edge $Ø D_c$	14 mm		
Overhang length L <sub>1</sub> incl. recess	36 mm		
Shank Ø D <sub>s</sub>	14 mm		
Helix angle	35 degrees		
Feed $f_z$ for side milling in short-chipping aluminium	0.2 mm		
Recess Ø D <sub>1</sub>	13 mm		
Balance quality with shank	G 2.5 with HA		
Direction of infeed	horizontal, oblique and vertical		
Tolerance nominal Ø	e8		

Overall length L	83 mm	
Feed $f_z$ for slot milling in short-chipping aluminium	0.18 mm	
Shank	DIN 6535 HA to h6	
No. of teeth Z	4	
Flute length $L_c$	26 mm	
Corner rounding r <sub>v</sub>	0.32 mm	
Series	Master Alu	
Coating	DLC	
Tool material	Solid carbide	
Standard	DIN 6527	
Milling profile	WR	
Helix angle characteristic	unequal spacing	
Spacing of the cutters	unequal spacing	
Cutting width $a_e$ for milling operation	0.4×D for side milling	
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D	
Through-coolant	no	
Machining strategy	HPC	
Colour ring	yellow	
Type of product	End / face mill	

### User data

	Suitability	V <sub>c</sub>	ISO code
Aluminium	Suitable	450 m/min	Ν
Aluminium (short chipping)	suitable	400 m/min	Ν
Alu > 10% Si	suitable	380 m/min	Ν
PA 66	suitable only under restricted conditions	120 m/min	Ν
РЕЕК	suitable only under restricted conditions	100 m/min	Ν

© Hoffmann GmbH Qualitätswerkzeuge

Cu	Suitable	160 m/min	Ν
CuZn	Suitable	200 m/min	Ν
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable only under restricted conditions		
Air Services	suitable		

Shank grinding Type HB

129100 HB