3M Roloc™

Coarse cleaning disc (SiC), Ø 50.8 mm, Fleece version: XCRS



Order data

Order number	554056 XCRS		
GTIN	50638060215383		
Item class	53M		

Description

Version:

Coarse cleaning disc with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad. Open structure, will not clog. **Stable edge, extremely high material removal rate and service life.** Ideal for removal of scale.

Application:

For rust removal, paint removal, dressing weld seams and removing surface dirt.

Technical description

3M designation	XT-DR		
maximum speed	18000 min ⁻¹		
Grit designation	extra coarse		
Disc Ø	50.8 mm		
Degree of hardness	very hard		
Grinding media	Silicon carbide (SiC)		
Grinding medium code	SiC		
Iron, sulphur and chlorine constituents	< 0.1 %		



Product name attribute	Ø 50.8 mm
Type of product	Rough cleaning non- woven abrasive mesh

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable		
Uni	suitable		
wet maximum	suitable only under restricted conditions		
dry	suitable		