

**Garant**
**GARANT Master Alu PickPocket solid carbide roughing end mill HPC, uncoated, Ø e8 DC: 7mm**

**Order data**

Order number	202002 7
GTIN	4062406125745
Item class	11X

**Description**
**Version:**

For roughing and finishing.

Up to  $2 \times D$  into solid material at very high feed rates and smooth cutting action.

Very high feed rates when plunging vertically.

Ramping capability up to  $45^\circ$ .

**Advantage:**

**Optimised flute form, eccentric relief ground, generous chip spaces.**

**Technical description**

No. of teeth Z	3
Overhang length $L_1$ incl. recess	25 mm
Tolerance nominal $\varnothing$	e8
Overall length L	63 mm
Helix angle	42 degrees
Feed $f_z$ for slot milling in short-chipping aluminium	0.07 mm
Shank $\varnothing D_s$	8 mm
Shank	DIN 6535 HA to h6
Feed $f_z$ for side milling in short-chipping aluminium	0.1 mm
Recess $\varnothing D_1$	6.8 mm

Cutting edge $\varnothing D_c$	7 mm
Flute length $L_c$	16 mm
Direction of infeed	horizontal, oblique and vertical
Balance quality with shank	G 2.5 with HA
Corner chamfer angle	90 degrees
Series	Master Alu
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End / face mill

## User data

	Suitability	$V_c$	ISO code
Aluminium	Suitable	250 m/min	N
Aluminium (short chipping)	suitable	200 m/min	N
Alu > 10% Si	Suitable	180 m/min	N
PMMA acrylic	Suitable	180 m/min	N
PE-HD	Suitable	130 m/min	N
PA 66	Suitable	150 m/min	N
PEEK	Suitable	130 m/min	N

PF 31	Suitable	110 m/min	N
Honeycomb sandwich	suitable only under restricted conditions	180 m/min	N
Cu	Suitable	120 m/min	N
CuZn	Suitable	150 m/min	N
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable only under restricted conditions		
<del>Air</del> <b>Services</b>	suitable		
Shank grinding Type HB			129100 HB