




Torque screwdriver fully insulated, Type: 4



Order data

Order number	659953 4
GTIN	4013288206398
Item class	63F

Description

Version:

Ergonomically shaped multi-component cross-head handle for optimum force transfer. Every screwdriver is preset to the **correct torque for each size of screw**. Drive size and torque are stamped on to the handle. When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. It is **not possible to tighten the screw any further**. The release torque is higher than the tightening torque (overload protection).

Handle and blade **fully insulated up to 1000 V** to **DIN EN 60900 / VDE 0682-201**.

Suitable for:

Hexagon socket head screws.

Technical description

Measurement process	Torque
set torque	500 cNm
Release signalling	haptic
Adjustable trigger value	non-adjustable
Torque measuring accuracy	±10 %
Series	400 i VDE

Connection format	exchangeable blade
Trigger principle	mechanical slip clutch
maximum torque	4 cNm
Direction of tightening	Right-hand tightening
Setting the trigger value	preset
Feedback	triggering
set torque	5 Nm
Weight	122 g
Measurement technology	mechanical
Overall length L	141 mm
Reversible reading	Nm
Blade length	93 mm
Data can be recorded	no
Drive profile	Hexagon screwdriver
Manufacturer's designation	400 i Hex
Torque fixed setting	yes
Type of product	Torque screwdriver