HOLEX

Carbide burr Z7 – medium, diamond cut Shank Ø 6 mm, Carbide, Type: AS1020



Order data

Order number	GG5075 AS1020	
GTIN	4045197730657	
Item class	GGN	

Description

Version:

Carbide burrs with high wear resistance and cutting edge stability. The shank is made of steel if the head \emptyset is larger than the shank \emptyset , otherwise it is of carbide. Z7 general-purpose tooth configuration for deburring, edge breaking, cleaning, weld dressing and surface preparation. Suitable for both manual and robot-mounted use.

Shank Ø 6 mm.

same as 540750. Cylindrical shape (ZYAS), with end cut.

Application:

Suitable for use with power tools and industrial robots, on almost all materials. For deburring, edge breaking, cleaning, weld and surface preparation.

Content:

10 burrs / drum.

Note:

Only sold in bulk pack quantities, not supplied individually. Ordering information: 1 set = 1 drum.

Technical description

A Hoffmann Group

Shape	AS1020		
Tooth type abbreviation	Ζ7		
Head length L ₁	19 mm		
Shank Ø	6 mm		
Type of cut	staggered teeth		
Overall length	64 mm		
Head Ø	9.5 mm		
Shape description	Cylinder med endefortanding		
Toothing grit designation	medium		
Contents	10		
Tool material	Carbide		
Type of product	Burr		

User data

	Suitability	V _c	ISO code
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
INOX	suitable only under restricted conditions		
Ti	suitable only under restricted conditions		
GG(G)	suitable		
Uni	suitable		

Accessories

BurrZ7 – medium, diamond cut Type AS1020

540750 AS1020