

## Carbide burr Z7 – medium, diamond cut Shank Ø 6 mm, Carbide, Type: C1625



### **Order data**

Order number	GG5075 C1625		
GTIN	4045197730725		
Item class	GGN		

### **Description**

#### **Version:**

**Carbide burrs** with high wear resistance and cutting edge stability. The shank is made of steel if the head  $\varnothing$  is larger than the shank  $\varnothing$ , otherwise it is of carbide. Z7 general-purpose tooth configuration for deburring, edge breaking, cleaning, weld dressing and surface preparation. Suitable for both manual and robot-mounted use.

Shank Ø 6 mm.

same as 540750.

### **Application:**

Suitable for use with power tools and industrial robots, on almost all materials. For deburring, edge breaking, cleaning, weld and surface preparation.

### **Content:**

10 burrs / drum.

#### Note:

Only sold in bulk pack quantities, not supplied individually. Ordering information: 1 set = 1 drum.

## **Technical description**

Head length L₁	25 mm		
Overall length	70 mm		
Type of cut	staggered teeth		
Shank Ø	6 mm		
Head ∅	16 mm		
Toothing grit designation	medium		
Shape	C1625		
Shape description	ball nose		
Tooth type abbreviation	Z7		
Contents	10		
Tool material	Carbide		
Type of product	Burr		

# **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Steel < 900 N/mm <sup>2</sup>	suitable		
Steel < 1400 N/mm <sup>2</sup>	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
INOX	suitable only under restricted conditions		
Ti	suitable only under restricted conditions		
GG(G)	suitable		
Uni	suitable		

## **Accessories**

BurrZ7 – medium, diamond cut Type C1625

540750 C1625