Garant GRIDUNE

Mobility unit retrofit set, suitable for casing depth in G: 28



Order data

Order number	958480 28
GTIN	4062406133498
Item class	9GK

Description

Version:

GridLine mobility unit consisting of 2 galvanised sheet metal cross beams. Completely assembled with set of wheels and 1 set of 2-component Haptoprene[®] push handle. For bolting on to GridLine cabinets and tool cabinets. **Push the cabinet from the side.**

For retrofitting to GridLine cabinets and tool cabinets.

Suitable for:

Tool cabinets No. 931005 – 931435, large-capacity cabinets No. 941001, 941003, 941021, 941023, 942301 – 942323, 942701 – 942723.

Supplied with:

 $1 \times$ cross beam with 2 castors with parking brakes, $1 \times$ cross beam with 2 fixed wheels, $1 \times$ push handle set.

Attention:

Because of the risk of tipping over, when installing the mobility unit comply strictly with the specified maximum cabinet height.

When calculating the load capacity, please take account of the tare weight of the cabinet / tool cabinet.

Note:

Mobility unit suitable for GridLine tool cabinets up to a maximum height of 1000 mm. Maximum overall load capacity of tool cabinets 600 kg. **Mandatory requirement that any drawers are fitted with one-hand individual drawer release.**

Mobility unit suitable for GridLine large-capacity cabinets up to a maximum height of 1000 mm. Maximum overall load capacity of large-capacity cabinets 200 kg. **Only for GridLine largecapacity cabinets without drawers.**

Technical description

Fixed wheel \varnothing	125 mm
Castor Ø	125 mm
Depth	700 mm
maximum load capacity	600 kg
Carriage height	160 mm
Type of product	Wheels and push handle