

HOLEX®
Solid carbide high performance drill Whistle-Notch shank DIN 6535 HE, TiN, Ø h7: 9,3 mm
Order data

Order number	123108 9,3
GTIN	4045197450722
Item class	12E

Description
Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

Recommendation:
Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

Note:
NEW GENERATION AVAILABLE!

Recommended successor product is No. 123109.

Tool material: Solid carbide

Drill depth up to: 8×D

Point angle: 135 degrees

Schaft: DIN 6535 HE to h6

Through-coolant: yes, with 25 bar

Norm: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

Flute length: 95 mm

Overall length L_{tot} : 142 mm

Shank Ø: 10 mm

Feed f in steel < 1100 N/mm²: 0.2 mm/rev.

Technical description

Machining strategy

Use for drilling	
Through-coolant	yes, with 25 bar
Pilot drill required	
Helix angle	degrees
Tool material	Solid carbide
Hole tolerance	
Point angle	135 degrees
Type	
Drill depth up to	8×D
Cutting direction	
Colour ring	green
Coating	TiN
Schaft	DIN 6535 HE to h6
Series	
Type of product	