Garant

Tool24 Smartline – upright cabinet fitted with tool sockets, for tool shanks: HSK63



Order data

| Order number | 979101 HSK63 |
|--------------|---------------|
| GTIN | 4062406134068 |
| Item class | 9SA |

Description

Version:

The pull-out shelves are supported from the base and equipped with central locking (can be used for emergency release). The end faces of the hot-dip galvanised frames of the pull-out shelves have holes at intervals of 37 mm for mounting tool stands, carrying rails, storage shelf trays, and perforated tool boards. The pull-out frames are equipped with an anti-tilt device. The pull-out frames open automatically. This ensures quick access to the tools.

- Storage of pre-set tools.
- · Only for use in conjunction with a Tool24 Smartline Master Unit system.
- Available with 14 different configurations (for different tool shanks SK, VDI, C, HSK).
- Supplied with 24 carrier rails.
- Mountings suitable for tool stands, support rails, shelf trays and perforated tool panels.
- Distributed safe working load per pull-out frame: 600 kg.
- Maximum upright cabinet load: 2400 kg.
- · Locking system for emergency release.

Application:

Automatic industrial vending solution for storage and management of tools and C-items. **Colour:**

Body RAL 7035 light grey, pull-out frames RAL 7016 anthracite powder-coated.

Note:

Upright cabinets place increased demands on the floor, since the pull-out frames run directly on the floor! The following pre-requirements for the installation site must be satisfied absolutely by the customer:

- Flatness tolerance for finished floors as per DIN 18202.
- Angularity of a maximum of 2 millimetres over the measurement length of 1 metre.
- $\cdot\,$ The subsurface must have a sufficient load-bearing capacity.
- $\cdot\,$ Only place on ground that is absolutely level.

The systems are prepared for wall or floor-mounting and must be secured against tilting. These upright cabinets can only be used in conjunction with a Tool24 Smartline Master Unit system No. 979001 S11M or No. 979001 S11M-EN, Tool24 PickOne Master Unit system No. 979201 DE or No. 979211 EN, and Tool24 Locker Master Unit system No. 979300 DE or No. 979310 EN.

Technical description

| Height | 2000 mm |
|--|---|
| Weight | 320 kg |
| Number of tool sockets | 336 |
| Number of pull-out frames | 4 |
| Pull-out frame drawers width | 155 mm |
| Axial spacing A | 76 mm |
| Number of tool carriers No. 970130 | 24 |
| Vertical pull-out frame usable height | 1750 mm |
| Width | 717 mm |
| Depth | 750 mm |
| Vertical pull-out frame load capacity | 600 kg |
| Series | Tool24 Smartline |
| Cabinet housing internal load capacity | 2400 kg |
| Drawer runner extension | Anti-tilt lock |
| Cylinder lock | modular lock barrel |
| Colour selection | RAL 9002, 7035, 7005, 7016, 6011, 5018, 5012, 5011, 5005, 3003 |
| Type of product | Tool issuing system |

Accessories

Tool carrier with tool sockets for tool shanks HSK63

970130 HSK63