

Electronic torque analyser "TruCheck™ 2", maximum torque: 1100N·m



Order data

Order number	654471 1100
GTIN	5060207566520
Item class	66D

Description

Version:

- · Compact, handy torque analyser.
- · Screw attachment to a flat surface (table, wall etc.).
- LCD display. LED background lighting ensures good legibility under poor lighting conditions.
- The integral micro-USB 2.0 port provides the power supply.
- · Units of measure: Nm.

Advantage:

- · Very easy to use (reduces errors).
- · Suitable even for users who are not "Calibration Specialists".
- · Only a single push button to zero the display.

Application:

Setting and testing triggering, indicating and right-hand triggering torque wrenches.

Accuracy:

Percentage measured value error $\pm 1\%$ for the measurement range 110-1100 Nm; $\pm 2\%$ for the measurement range less than 110 Nm.

Supplied with:

USB power supply unit (EU/UK/US/AUS), micro USB 2.0 cable, in sturdy plastic case.

Technical description



maximum torque	1100 Nm
Measuring range	50 - 1100 Nm
Display unit depth	132.5 mm
Square drive adapter	3/4 in
Display unit width	140 mm
Weight	3.5 kg
Display unit height	120 mm
Torque measuring accuracy	± 1 %
Torque measuring accuracy	±2 %
Power supply	Mains operated
Nominal voltage	100 - 240 V
External hexagon drive	27 mm
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Calibration	04
Type of product	Torque testing device

Services

Calibration, clockwiseTorque analyser / sensor Type 1000	020120 1000
--	-------------