

Three-jaw lathe chuck cast-iron with recessed mount, DIN 702-4, External \varnothing A: 250mm



Order data

Order number	312906 250
GTIN	4062406154547
Item class	32W

Description

Version:

- · Manual chucks with gear scroll, centrically clamping.
- · Body made of cast iron or steel.
- · Gear scroll drop-forged, balanced, and hardened.
- · Flanks of scroll and of jaw serrations are ground.
- · High concentricity, more precise than DIN 6386 requirement.

Application:

For machine spindles with recessed centring mount or for mounting using a flange. The chuck is secured from the rear by means of screws. The flange blanks must always be fitted first to the machine and then to the chuck.

Standard:

DIN 702-4.

Supplied with:

Includes: 1 set = 3 hardened inside jaws, stepped on the outside.

1 set = 3 hardened outside jaws, stepped on the inside.

1 clamping wrench and fastening screws or studs depending on the chuck.

Optional extras:

Spare and additional jaws No. 312971 – 312986.

Technical description

Centring ∅ B	200 mm
External Ø A	250 mm
Centring depth C	5 mm
Weight	29 kg
Aperture E	76 mm
Height with jaws H ₂	119 mm
maximum speed	2500 min ⁻¹
Height without jaws H ₁	85 mm
Standard	DIN 702-4
Material	Cast iron
Colour code for accessories	HOLEX geared scroll chucks and jaws
Type of product	Gear scroll chucks

Accessories

Workpiece backstop Height h 15 mm	313033 15
Workpiece back-stop, base module Height h 15 mm	313036 15
Scroll jaw set, 3 pieces, soft for chuck type 250	312971 250
Inside jaw set, 3 pieces, hardened for chuck type 250	312986 250
Top jaw set, 3 pieces, soft for chuck type 250	312981 250
Base jaw set, 3 pieces, hardened for chuck type 250	312976 250