#### Garant GRIDUNG

## ESD media track for individual configuration, suitable for type: 1500



## **Order data**

Order number	972200 1500
GTIN	4062406167554
Item class	9GW

## **Description**

#### Version:

Of sheet metal **modular design.** All power components include **cables** and **plugs.** The modules and covers can be changed / positioned as desired.

•Cable slots are provided on the upper, lower, and end faces for power supplies and for linking multiple media tracks together.

## Electrical pre-installation with industrial plug-in system (applies only to media tracks):

1 pc. distribution block No. 928492 with 5-pin feed/supply cable and 5 pcs. 3-pin sockets, 1 pc. 5-pin plug connector No. 928490 size 5 included for the feed cable.

### **Description:**

Technical data for industrial plug-in system (No. 928490; 928491; 928492):

- Maximum connection value 230 V / AC, 16 A or 400 V / AC, 16 A.
- Total load capacity at AC: 3.5 kW.
- · Maximum connected load, three-phase AC: 10.5 kW.
- · Conductor cross-section of the pre-assembled cables:
  - $3 \times 1.5 \text{ mm}^2$  for single-phase AC (L, N, PE)
  - 5 × 1.5 mm<sup>2</sup> for three-phase AC (L1, L2, L3, N, PE)
- · Protection class 1
- · Index of Protection IP 20.

#### **Suitable for:**

Support columns No. 972080. Installation by insertion.

#### **Colour:**

Light grey similar to RAL 7035 ESD powder-coated.

#### **Note:**

- · All plastic components (e.g. covering caps) are not ESD conductive.
- · Initial connections and also the connection of plugs and sockets to cables should be performed only by a qualified electrician!
- For information on the technical data of the industrial plug-in system, see eShop www.hofmann-group.com under the appropriate article number.



# **Technical description**

2×/1×/3×
1420 mm
1500
13 units
160 mm
250 V
GST plug-in system
no
AC
1.5 mm
EGB/ESD
Power module