Garant GRIDUINE

ESD media track with 2 sockets 250V, suitable for type: 1500



Order data

| Order number | 972201 1500 |
|--------------|---------------|
| GTIN | 4062406167585 |
| Item class | 9GW |

Description

Version:

Of sheet metal **modular design.** All power components include **cables** and **plugs.** The modules and covers can be changed / positioned as desired.

•Cable slots are provided on the upper, lower, and end faces for power supplies and for linking multiple media tracks together.

Electrical pre-installation with industrial plug-in system (applies only to media tracks):

1 pc. distribution block No. 928492 with 5-pin feed/supply cable and 5 pcs. 3-pin sockets,

1 pc. 5-pin plug connector No. 928490 size 5 included for the feed cable.

Description:

Technical data for industrial plug-in system (No. 928490; 928491; 928492):

- $\cdot\,$ Maximum connection value 230 V / AC, 16 A or 400 V / AC, 16 A.
- Total load capacity at AC: 3.5 kW.
- Maximum connected load, three-phase AC: 10.5 kW.
- · Conductor cross-section of the pre-assembled cables:
- 3 × 1.5 mm² for single-phase AC (L, N, PE)
- 5 × 1.5 mm² for three-phase AC (L1, L2, L3, N, PE)
- · Protection class 1
- · Index of Protection IP 20.

Suitable for:

Support columns No. 972080. Installation by insertion.

Colour:

Light grey similar to RAL 7035 ESD powder-coated.

Note:

- All plastic components (e.g. covering caps) are not ESD conductive.
- Initial connections and also the connection of plugs and sockets to cables should be performed only by a qualified electrician!
- For information on the technical data of the industrial plug-in system, see eShop www.hofmann-group.com under the appropriate article number.

Technical description

| suitable for type | 1500 |
|------------------------------|--------------------|
| Width | 1420 mm |
| Divider unit | 13 units |
| Installation height | 160 mm |
| Nominal voltage | 250 V |
| On/Off switch | no |
| Plug type, input | GST plug-in system |
| Number of sockets type F | 2 |
| Socket type | F |
| Type of current | AC |
| Material thickness | 1.5 mm |
| electrostatic characteristic | EGB/ESD |
| Type of product | Power module |

Accessories

ESD module for energy and media Module type DE250V/1

972220 DE250V/1