

## Garant

### GARANT Master Steel PickPocket solid carbide roughing end mill HPC, TiAlN, Ø f8 DC: 13,7 mm



#### Order data

Order number	202406 13,7
GTIN	4045197781468
Item class	11X

#### Description

##### Version:

For **roughing and finishing**

With corner radii similar to torus cutters.

Up to 1xD into solid material **at very high feed rates** with smooth cutting action.

##### Advantage:

Optimised flute form, eccentric relief ground, wide chip space.

Tolerance nominal Ø: f8

No. of teeth Z: 3

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length  $L_c$ : 26 mm

Overhang length  $L_1$  incl. recess: 52 mm

Recess Ø  $D_1$ : 13.3 mm

Overall length L: 99 mm

Shank Ø  $D_s$ : 14 mm

#### Technical description

Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.1 mm
Cutting edge Ø $D_c$	13.7 mm
Recess Ø $D_1$	13.3 mm
Flute length $L_c$	26 mm

Direction of infeed	horizontal, oblique and vertical
Overhang length $L_1$ incl. recess	52 mm
Overall length L	99 mm
Shank $\varnothing D_s$	14 mm
Tolerance nominal $\varnothing$	f8
No. of teeth Z	3
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.08 mm
Shank	DIN 6535 HB to h6
Helix angle	38 degrees
Corner rounding $r_v$	0.69 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	0.4×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill