Garant

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 11,6mm

Status

Order data

Order number	122715 11,6		
GTIN	4045197788535		
Item class	11E		

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low power output** and high speeds.

- · Clear reduction in cutting forces due to special cutter geometry.
- $\cdot\,$ Coating for best wear resistance even at high process temperatures.

· Polished flutes for good chip clearance.

A slim chisel edge and the special arrangement of the 4 guide chamfers ensure high

positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$. Form HB and HE supplied at the same price as HA. Form **HB:** order with **No. 122716**. Form **HE:** order with **No. 122715 + 129100HE**.

Technical description

Standard	DIN 6537		
Overall length L	118 mm		
Nominal Ø D _c	11.6 mm		
Shank Ø D _s	12 mm		
Tolerance nominal Ø	h7		
Flute length L_c	71 mm		

Number of cutting edges Z	2		
Feed f in steel < 1100 N/mm ²	0.28 mm/rev.		
recommended maximum drilling depth L_2	53.6 mm		
Series	Master Steel		
Coating	TiAIN		
Tool material	solid carbide		
Version	6×D		
Point angle	135 degrees		
Shank	DIN 6535 HA to h6		
Through-coolant	yes, with 25 bar		
Machining strategy	HPC		
Semi-Standard	yes		
Colour ring	green		
Type of product	Jobber drill		

User data

	Suitability	Vc	ISO code
Steel < 500 N/mm ²	suitable	220 m/min	Р
Steel < 750 N/mm ²	suitable	200 m/min	Р
Steel < 900 N/mm ²	suitable	180 m/min	Р
Steel < 1100 N/mm ²	suitable	170 m/min	Р
Steel < 1400 N/mm ²	suitable	90 m/min	Р
INOX < 900 N/mm ²	suitable only under restricted conditions	75 m/min	М
GG	suitable	160 m/min	К
GGG	suitable	130 m/min	К
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		

© Hoffmann GmbH Qualitätswerkzeuge

Services

Shank grinding Type HE

129100 HE