

Garant

Solid carbide special drill DIN 6535 HA, uncoated, Ø DC ±0.003: 12,04-Xmm



Order data

| | |
|--------------|----------------|
| Order number | 121201 12,04-X |
| GTIN | 4062406200589 |
| Item class | 11E |

Description

Version:

Spiral flute precision drill for plastics. **Self-centring** with **1-cutter geometry**, achieves **very high alignment accuracy**. **Polished** helical flutes for **optimum chip evacuation**.

Maintains the **tolerance band IT7** from entry Ø through to exit Ø, **due to special point geometry**.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

HB and HE shanks are available at the same price as HA.

For **HB shanks**: use order **No. 121201 + 129100HB**.

For **HE shanks**: use order **No. 121201 + 129100HE**. Delivery time: 8 weeks

Minimum order quantity: 3 pcs.

Items made to order for a specific customer: Cancellation only up to a maximum of 3 working days after receipt of order acknowledgement. Items cannot be returned. We reserve the right to over or under deliver by +/-10% (min. 1 pc).

Technical description

| | |
|-----------------------------|------------------|
| Overall length L | 124 mm |
| Ø range | 12.04 - 13.03 mm |
| Shank Ø D _s | 14 mm |
| Number of cutting edges Z | 1 |
| Flute length L _c | 77 mm |
| Standard | DIN 6537 |
| Tolerance nominal Ø | ±0.003 |

| | |
|-----------------|-------------------|
| Coating | uncoated |
| Tool material | Solid carbide |
| Version | 5×D |
| Point angle | 120 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | no |
| Semi-Standard | yes |
| Colour ring | without |
| Type of product | Jobber drill |

User data

| | Suitability | V _c | ISO code |
|--------------|---|----------------|----------|
| PMMA acrylic | suitable | 30 m/min | N |
| PE-HD | suitable | 50 m/min | N |
| PA 66 | suitable | 50 m/min | N |
| PEEK | suitable | 50 m/min | N |
| PF 31 | suitable | 50 m/min | N |
| PVDF GF20 | suitable only under restricted conditions | 60 m/min | N |
| POM GF25 | suitable only under restricted conditions | 60 m/min | N |
| PA 66 GF30 | suitable only under restricted conditions | 60 m/min | N |
| PEEK GF30 | suitable only under restricted conditions | 50 m/min | N |
| PTFE CF25 | suitable only under restricted conditions | 40 m/min | N |
| PEEK CF30 | suitable only under restricted conditions | 40 m/min | N |
| wet maximum | suitable only under restricted conditions | | |

| | |
|-----|----------|
| dry | suitable |
| Air | suitable |