


# Flap wheel (A), 80 grit, Head Ø×head width: 3/30X10mm



### **Order data**

| Order number | 554200 3/30X10 |  |  |
|--------------|----------------|--|--|
| GTIN         | 4045197803283  |  |  |
| Item class   | 52E            |  |  |

## **Description**

#### **Version:**

Flap strips bonded on to the shank of the tool.

Abrasive strips covered with **Aluminium Oxide (A)**.

#### **Application:**

Primarily for finish grinding and polishing tasks on larger radii in tool and mould making, for vessel and machine fabrication. The abrasive strips adapt to the contours of the component.

## **Technical description**

| Shank Ø                | 3 mm                     |  |  |
|------------------------|--------------------------|--|--|
| Grit                   | 80                       |  |  |
| Head ∅                 | 30 mm                    |  |  |
| maximum speed          | 18000 min <sup>-1</sup>  |  |  |
| recommended speed      | 16000 min <sup>-1</sup>  |  |  |
| Head width             | 10 mm                    |  |  |
| Grinding media         | Aluminium Oxide grit (A) |  |  |
| Grinding medium code   | Α                        |  |  |
| Product name attribute | 80 grit                  |  |  |



Type of product Flap wheel

# **User data**

|                                | Suitability                               | <b>V</b> <sub>c</sub> | ISO code |
|--------------------------------|---|-----------------------|----------|
| Alu Mg                         | suitable                                  |                       |          |
| Steel < 900 N/mm <sup>2</sup>  | suitable                                  |                       |          |
| Steel < 1400 N/mm <sup>2</sup> | suitable only under restricted conditions |                       |          |
| Steel < 55 HRC                 | suitable                                  |                       |          |
| Steel < 60 HRC                 | suitable only under restricted conditions |                       |          |
| GG(G)                          | suitable only under restricted conditions |                       |          |
| CuZn                           | suitable                                  |                       |          |
| Plastic, GRP                   | suitable                                  |                       |          |
| Wood                           | suitable                                  |                       |          |
| dry                            | suitable                                  |                       |          |