



Flap wheel Fleece (A), coarse, Head \varnothing ×head width: 60X50mm



Order data

Order number	554950 60X50
GTIN	4045197803917
Item class	52E

Description

Version:

Flap strips of fleece around the shank of the tool. Shank \varnothing 6 mm.

Fleece impregnated with Aluminium Oxide (A). Creates a **consistent matt finish**.

Application:

For removal of dirt and oxide layers on metals as well as for matt finishing of Cr-Ni, other stainless steels, and also non-ferrous metals.

Technical description

recommended speed	5000 min ⁻¹
Head width	50 mm
Head \varnothing	60 mm
maximum speed	9000 min ⁻¹
Shank \varnothing	6 mm
Grinding medium code	A
Grit equivalent	100
Grit designation	coarse
Product name attribute	coarse

Type of product

Flap wheel

User data

	Suitability	V_c	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable only under restricted conditions		
Steel < 67 HRC	suitable only under restricted conditions		
INOX	suitable		
Ti	suitable only under restricted conditions		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Paint	suitable only under restricted conditions		
dry	suitable		