

Flap wheel Fleece (SiC), coarse, Head Ø×head width: 40X20mm



Order data

Order number	554971 40X20		
GTIN	4045197803955		
Item class	52E		

Description

Version:

Flap strips of fleece around the shank of the tool. Shank \emptyset 6 mm.

The sharp-edged silicon carbide grit (SiC) provides aggressive grinding characteristics and a **slightly lustrous finish.**

Application:

For removal of dirt and oxide layers on metals as well as for matt finishing of Cr-Ni, other stainless steels, and also non-ferrous metals.

Technical description

Head width	20 mm		
maximum speed	14000 min ⁻¹		
Head ∅	40 mm		
Shank Ø	6 mm		
recommended speed	7500 min ⁻¹		
Grinding media	Silicon carbide		
Grinding medium code	SiC		



Grit equivalent	100	
Grit designation	coarse	
Product name attribute	coarse	
Type of product	Flap wheel	

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable only under restricted conditions		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable only under restricted conditions		
dry	suitable		