Garant

GARANT Master Tap machine tap HSS-E-PM, AITiX, UNF: 5-44



Order data

Order number	133410 5-44	
GTIN	4062406208707	
Item class	111	

Description

Version:

GARANT Master Tap general-purpose tap, designed for use on a wide spectrum of materials with high process reliability.

- HSS-E-PM tool material for maximum wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Application:

For UNF unified fine threads ASME – B1.1.

Thread type: UNF Tool material: HSS E PM Standard: DIN 371 Threads per inch: 44 Thread \emptyset : 3.17 mm Overall length L: 56 mm Shank \emptyset D_s: 3.5 mm Shank square \Box : 2.7 mm Tapping hole \emptyset : 2.7 mm

Technical description

Standard	DIN 371
Thread type	UNF
Tapping hole Ø	2.7 mm
Shank square 🗆	2.7 mm
Tool material	HSS E PM

© Hoffmann GmbH Qualitätswerkzeuge

Thread size	5-44 UNF		
Threads per inch	44		
Thread Ø	3.17 mm		
Shank Ø D _s	3.5 mm		
Thread pitch	0.577 mm		
Number of cutting edges Z	3		
Thread depth	9.51 mm		
Number of clamping slots	3		
Overall length L	56 mm		
Series	Master Tap		
Coating	AITiX		
Flank angle	60 °		
Tolerance class	2BX		
Taper lead form	В		
Shank	Plain shank with h9		
Through-coolant	no		
Application for type of drilling	up to 3×D for through holes		
Cutting direction	right-hand		
Type of threading tool	Machine tap for dynamic machining		
Colour ring	green		
Type of product	Тар		

User data

	Suitability	V _c	ISO code
Alu plastics	suitable	30 m/min	Ν
Aluminium (short chipping)	suitable	35 m/min	Ν
Alu > 10% Si	suitable	20 m/min	Ν
Steel < 500 N/mm ²	suitable	30 m/min	Р

© Hoffmann GmbH Qualitätswerkzeuge

Steel < 750 N/mm ²	suitable	30 m/min	Р
Steel < 900 N/mm ²	suitable	25 m/min	Р
Steel < 1100 N/mm ²	suitable	12 m/min	Р
Steel < 1400 N/mm ²	suitable	8 m/min	Р
INOX < 900 N/mm ²	suitable	10 m/min	М
INOX > 900 N/mm ²	suitable	8 m/min	М
GG(G)	suitable	20 m/min	К
CuZn	suitable	20 m/min	Ν
Uni	suitable		
Oil	suitable		
wet maximum	suitable		