

**Garant**
**GARANT Master Tap machine tap HSS-E-PM, ALTiX, UNF: 8-36**

**Order data**

Order number	133410 8-36
GTIN	4062406208721
Item class	111

**Description**
**Version:**

**GARANT Master Tap general-purpose tap**, designed for use on a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

**Application:**

**For UNF unified fine threads ASME – B1.1.**

Thread type: UNF

Tool material: HSS E PM

Standard: DIN 371

Threads per inch: 36

Thread Ø: 4.16 mm

Overall length L: 63 mm

Shank Ø D<sub>s</sub>: 4.5 mm

Shank square □: 3.4 mm

Tapping hole Ø: 3.5 mm

**Technical description**

Tapping hole Ø	3.5 mm
Shank square □	3.4 mm
Thread size	8-36 UNF
Shank Ø D <sub>s</sub>	4.5 mm
Thread Ø	4.16 mm

Number of cutting edges Z	3
Overall length L	63 mm
Threads per inch	36
Thread depth	12.48 mm
Thread type	UNF
Thread pitch	0.705 mm
Standard	DIN 371
Number of clamping slots	3
Tool material	HSS E PM
Series	Master Tap
Coating	AlTiX
Flank angle	60°
Tolerance class	2BX
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap

## User data

	Suitability	V <sub>c</sub>	ISO code
Alu plastics	suitable	30 m/min	N
Aluminium (short chipping)	suitable	35 m/min	N
Alu > 10% Si	suitable	20 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	30 m/min	P

Steel < 750 N/mm <sup>2</sup>	suitable	30 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	25 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	12 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable	8 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable	10 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable	8 m/min	M
GG(G)	suitable	20 m/min	K
CuZn	suitable	20 m/min	N
Uni	suitable		
Oil	suitable		
wet maximum	suitable		