

**Garant**
**GARANT Master Tap SteelHT machine tap HSS-E-PM Form B, TiCN, G: G3/4**

**Order data**

Order number	133312 G3/4
GTIN	4062406236748
Item class	11I

**Description**
**Version:**

High-performance tap, specially developed for use in **steels with high tensile strength** and for **difficult-to-machine materials**. **Strong spiral point**, for process stability at high cutting forces.

- **HSS-E-PM tool material – for very high cutting edge stability.**
- **Optimised honed cutting edges.**
- **TiCN coating – for maximum wear protection.**

**Application:**

**For Whitworth parallel pipe threads** DIN-ISO 228/1 (threads that do not form a seal within the connection).

**Recommendation:**

For **TOOLOX** and **HARDOX** materials we recommend **deviating from the DIN data** (see table) **by selecting a larger tapping hole diameter.**

**Technical description**

Tapping hole $\varnothing$	24.5 mm
Number of clamping slots	4
Number of cutting edges Z	4
Shank square $\square$	16 mm
Shank $\varnothing D_s$	20 mm
Thread $\varnothing$	26.44 mm
Thread depth	79.32 mm
Tool material	HSS E PM

Overall length L	140 mm
Thread size	G3/4
Thread pitch	1.814 mm
Threads per inch	14
Series	Master Tap
Coating	TiCN
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap

## User data

	Suitability	V <sub>c</sub>	ISO code
Steel < 750 N/mm <sup>2</sup>	suitable only under restricted conditions	30 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	20 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	15 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable	12 m/min	P
Steel < 50 HRC	suitable only under restricted conditions		
TOOLOX 33	suitable	15 m/min	H
TOOLOX 44	suitable		

INOX > 900 N/mm <sup>2</sup>	suitable
Ti > 850 N/mm <sup>2</sup>	suitable only under restricted conditions
Oil	suitable
wet maximum	suitable