

## Garant

### GARANT Master Tap SteelHT machine tap HSS-E-PM Form C 6GX, TiAlN, M: M6



#### Order data

Order number	135374 M6
GTIN	4062406237028
Item class	11I

#### Description

##### Version:

High-performance tap, specially developed for use in **steels with high tensile strength** and for **difficult-to-machine materials**. Sturdy design with **optimised guide thread to avoid chips jamming**.

- **HSS-E-PM tool material – for very high cutting edge stability.**
- **Optimised honed cutting edges.**
- **TiAlN coating – for maximum wear protection.**

**Tolerance class: ISO 3X/6GX.**

##### Application:

For components which are galvanised or shrink slightly when hardened.

##### Recommendation:

For **TOOLOX** and **HARDOX** materials we recommend deviating from the **DIN data** (see table) by **selecting a larger tapping hole  $\varnothing$** .

##### Note:

For **TOOLOX** and **HARDOX** materials: do not exceed the maximum thread depth  $2 \times D!$

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 3X 6GX

Thread pitch: 1 mm

Overall length L: 80 mm

Shank  $\varnothing D_s$ : 6 mm

Shank square  $\square$ : 4.9 mm

Tapping hole  $\varnothing$ : 5 mm

#### Technical description

Tool material	HSS E PM
Standard	DIN 371
Thread $\varnothing$	6 mm
Thread depth	15 mm
Tolerance class	ISO 3X 6GX
Shank square $\square$	4.9 mm
Shank $\varnothing D_s$	6 mm
Thread type	M
Tapping hole $\varnothing$	5 mm
Number of cutting edges Z	3
Number of clamping slots	3
Thread pitch	1 mm
Thread size	M6
Overall length L	80 mm
Coating	TiAlN
Flank angle	60°
Thread standard	DIN 13
Taper lead form	C
Helix angle	40°
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Series	Master Tap
Type of product	Tap

## User data

	Suitability	$V_c$	ISO code
--	-------------	-------	----------

Steel < 750 N/mm <sup>2</sup>	suitable only under restricted conditions	30 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	20 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	15 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable	12 m/min	P
Steel < 50 HRC	suitable only under restricted conditions		
TOOLOX 33	suitable	15 m/min	H
TOOLOX 44	suitable		
HARDOX 500 < 1600 N/mm <sup>2</sup>	suitable only under restricted conditions		
INOX > 900 N/mm <sup>2</sup>	suitable		
Ti > 850 N/mm <sup>2</sup>	suitable only under restricted conditions		
Oil	suitable		
wet maximum	suitable		