



### Diabolo solid carbide HPC drill, plain shank DIN 6535 HA, TiAlN, Ø h7: 14 mm

# **Order data**

Order number	122536 14
GTIN	4045197541314
Item class	11E

## **Description**

#### **Version:**

**GARANT Diabolo** – cutting chisel edge with high centring accuracy – due to special point geometry and strong core. Convex major cutting edges with slightly honed edges and special flute profile for short chips.

**Special coating** for drilling in hardened steels.

**Recommendation:** 

### Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.1

#### Note:

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 122538.

Form **HE:** order with **No. 122536 + 129100HE**.

Tool material: Solid carbide Drill depth up to: 6×D

Type: H

Point angle: 140 degrees Skaft: DIN 6535 HA to h6 Machining strategy: HPC

Norm: DIN 6537

Tolerance nominal Ø: h7 Number of cutting edges Z: 2 Tolerance nominal Ø: h7 Flute length: 77 mm

Overall length L<sub>tot</sub>: 124 mm

Shank Ø: 14 mm

Feed f in steel < 60 HRC: 0.13 mm/rev.

## **Technical description**



Tool material	Solid carbide
Hole tolerance	
Colour ring	red
Through-coolant	
Helix angle	degrees
Point angle	140 degrees
Coating	TiAlN
Drill depth up to	6×D
Cutting direction	
Pilot drill required	
Machining strategy	HPC
Туре	Н
Use for drilling	
Skaft	DIN 6535 HA to h6
Series	Diabolo
Type of product	