

## Driven tool, radial, ER32, Type: 40-32-RIKD



## Order data

Order number	319921 40-32-RIKD
GTIN	
Item class	31W

# **Description**

#### **Version:**

For use on **disc turrets**. Right-hand version. Ratio 1:1. Version with internal cooling (internal) max. 70 bar. Alignment using **standard-pin bar**.

For use on all **DMG Gildemeister CTX** CNC lathes with **Sauter** turret. Drive coupling **DIN 5480**. Clamping of tools in driven tool using ER collet with external nut or VARIA VX quick-change system under license from EWS. External cooling via a coolant tube, internal cooling through the tool centrally through the spindle. Maximum speed 8000 rpm.

Version IKD – with ceramic seal set, pressures up to 70 bar, with full dry-run capability. Version IM – with internal clamping nut.

#### **Advantage:**

- · Weight- and geometry-optimized design.
- · Process reliability through high-quality components, longevity.
- · High torque transmission.
- 100% control each driven tool is subjected to a run-in programme.
- · Internal cooling: specially developed and patented seal.

#### **Application:**

As many machining steps as possible in one clamping set-up. Where space (available clamping positions) in the revolver is at a premium.

#### **Suitable for:**

DMG Gildemeister CTX. In some cases, Emco, Hardinge, Monforts, Scherer etc. with DIN 5480.

### **Supplied with:**



Driven tool for collet: including clamping nut and hook spanner. Driven tool VARIA VX: including chuck key.

## **Optional extras:**

Suitable inserts Varia VX No. 319802 – 319888, ER quick-change adapters No. 319761 – 319781, ER collets No. 308941 – 309878, ER clamping wrenches No. 309680 – 309745.

#### Note:

- Other drive types (such as DIN 5482), ratios, dimensions, BMT etc. on request, see: www.hoffmann.ews-tools.com
- $\cdot$  IC tools (with through cooling) will not run dry with standard seal, coolant filtering < 50  $\,$  µm.
- · Recommendation: Tighten version VARIA VX with a torque tool (max. 6 Nm).
- For heavy-duty milling work, a variant with tapered roller bearings is recommended on request.

# **Technical description**

$b_1$	85 mm
	138 mm
$\mathbf{h}_1$	76 mm
X	100 mm
Cooling	internal
$b_2$	53 mm
Adapter	ER32
VDI size	40
Tool clamping	ER32
Type of product	Driven tool

### **Accessories**

Varia collet chuck VARIA VX4 for ER collet size 32	319804 32
Varia collet chuck VARIA VX3 for ER collet size 32	319802 32