

### Driven tool, radial, TOEM rail, ER25, Type: 30-25-LIKD



# **Order data**

Order number	319939 30-25-LIKD
GTIN	
Item class	31W

## **Description**

### **Version:**

Stop rail (42.5 TOEM).

Version IKD – with ceramic seal set, pressures up to 70 bar, with full dry-run capability.

For use on all **DMG Gildemeister CTX** CNC lathes with **Sauter** turret. Drive coupling **DIN 5480**.

Clamping of tools in driven tool using ER collet with external nut or VARIA VX quick-change system under license from EWS. External cooling via a coolant tube, internal cooling through the tool centrally through the spindle. Maximum speed 8000 rpm.

For use on **disc turrets**. Left-hand version, i.e. machining in the direction of the main spindle. Ratio 1:1. Version with internal cooling (internal) max. 70 bar.

#### **Advantage:**

- · Weight- and geometry-optimized design.
- · Process reliability through high-quality components, longevity.
- High torque transmission.
- · 100% control each driven tool is subjected to a run-in programme.
- · Internal cooling: specially developed and patented seal.

### **Application:**

As many machining steps as possible in one clamping set-up. Where space (available clamping positions) in the revolver is at a premium.

#### **Suitable for:**

DMG Gildemeister CTX. In some cases, Emco, Hardinge, Monforts, Scherer etc. with DIN 5480.

### **Supplied with:**

Driven tool for collet: including clamping nut and hook spanner. Driven tool VARIA VX: including chuck key.

### **Optional extras:**

Suitable inserts Varia VX No. 319802 – 319888, ER quick-change adapters No. 319761 – 319781, ER collets No. 308941 – 309878, ER clamping wrenches No. 309680 – 309745.

#### Note:

- Other drive types (such as DIN 5482), ratios, dimensions, BMT etc. on request, see: www.hoffmann.ews-tools.com
- · IC tools (with through cooling) will not run dry with standard seal, coolant filtering < 50 um.
- · Recommendation: Tighten version VARIA VX with a torque tool (max. 6 Nm).
- · For heavy-duty milling work, a variant with tapered roller bearings is recommended on request.

# **Technical description**

$b_1$	67 mm
Cooling	internal
X	100 mm
	126 mm
$b_2$	59.5 mm
$\mathbf{h}_1$	64 mm
Adapter	ER25
VDI size	30
Tool clamping	ER25
Type of product	Driven tool

### **Accessories**

Varia collet chuck VARIA VX4 for ER collet size 25	319804 25
Varia collet chuck VARIA VX3 for ER collet size 25	319802 25