

Magnetic gripper, Ø D: 80mm



Order data

| Order number | 358711 80 |
|--------------|---------------|
| GTIN | 4062406241773 |
| Item class | 31V |

Description

Version:

- · Optimised and safe working procedure.
- Collision protection when approaching thanks to compression spring safety compensation of 10mm.
- By exchanging the inserts, individual workpiece geometries can be automatically separated, transported and stored.
- · Machine running times without long interruptions.
- · High efficiency due to optimised utilisation.
- · Significantly less contamination by oil mist.
- · Permits unmanned operation.
- · Reduces the risk of injuries.
- · Can be used in all commonly-used Weldon arbors.

Application:

The tool can lift and release ferro-magnetic workpieces. Activation of the magnet by coolant (IKZ) or compressed air. Positive engagement of the machined workpiece by closure with the matching contour of the exchangeable plate, for transport to the desired destination within the machine room.

Supplied with:



Supplied with exchangeable plate 358716 with height 20 mm. Supplied with spring and clamping screw for the Weldon arbor.

Technical description

| \emptyset D ₁ | 20 mm |
|----------------------------|-------------------|
| Ø D | 80 mm |
| Height H ₂ | 48.5 mm |
| Height H₃ | 12 mm |
| Height H ₁ | 98.5 mm |
| Magnet Ø | 10 mm |
| Magnet retaining force | 4.5 kg |
| Operation mode | Compressed air |
| Operation mode | Cooling lubricant |
| maximum operating pressure | 50 bar |
| minimum operating pressure | 30 bar |
| Type of product | Magnetic gripper |

Accessories

| Interchangeable insert for magnetic gripper, PA \varnothing / height 80/40 mm | 358716 80/40 |
|--|--------------|
| Interchangeable insert for magnetic gripper, aluminium \varnothing / height 80/20 mm | 358717 80/20 |
| Interchangeable insert for magnetic gripper, PA \varnothing / height 80/20 mm | 358716 80/20 |
| Interchangeable insert for magnetic gripper, aluminium Ø / height 80/40 mm | 358717 80/40 |