



Dry film separating agent NSR Dry, Contents: 500ml



Order data

Order number	083088 500
GTIN	5412386064968
Item class	08E

Description

Version:

Universal silicone-free dry film separating agent for thermoset resins and thermoplastics, especially for rubberised plastics or plastics subject to stress cracking.

- **Dry film moulded part separating agent, on a wax/ester basis.**
- **Silicone-free, minimises material carry-over on to moulded parts. Ideal for moulded parts with a further processing stage (painting, printing or adhesively bonded).**
- **Operating temperature range up to 150 °C.**

Application:

To assist the release from the mould of rubberised plastics, thermoset resins and thermoplastics, especially plastics subject to stress cracking such as PC, PS, PET or PMMA. Anti-friction and separating agent for sliding tracks, textiles, foams etc.

- **Apply a thin even film to the clean dry mould.**
- **Wait a short time until the solvent has evaporated.**
- **For sustained separation effect, repeat the process.**
- **Refer to the current safety data sheet (SDB) for safety instructions.**

Technical description

Solubility in water	insoluble
Labelling of hazardous substances	GHS02: Flame
Labelling of hazardous substances	GHS07 caution
Labelling of hazardous substances	GHS09 harmful to the environment
Spray head	Standard
Colour	transparent
hazardous goods class	2.1
Contents	500 ml
Version	Spray can
Type of product	Parting agent