

**Wet film separating agent containing silicone SR Multi, Contents: 500ml**

Order data

Order number	083089 500
GTIN	5412386064975
Item class	08E

Description**Version:**

General-purpose moulded part separating agent containing silicone, for plastics processing. Outstanding separating performance on thermoset resins and thermoplastics, and also on many types of rubber.

- **Excellent separation and anti-friction effect.**
- **Improves surface quality.**
- **Reduces scrap rates for machining if plastic moulded parts, and increases productivity.**
- **Does not accumulate in the mould.**
- **Operating temperature range up to 200°C.**

Application:

To assist the release of plastic and rubber moulded parts from the injection mould, in vacuum forming and many other processes for plastics processing. As anti-friction and separating agent for sliding tracks, textiles, foams etc.

- **Apply a thin even film to the clean dry mould at a distance of 25 – 30 cm.**
- **Wait a short time until the solvent has evaporated.**
- **If necessary, repeat the procedure after some time.**
- **Refer to the current safety data sheet (SDB) for safety instructions.**

Note:

Contains silicone, which achieves a high and sustained separation effect. On some cases this may have a negative effect on the moulded parts regarding adhesion of paints, coating or adhesives.

Technical description

Solubility in water	insoluble
Contents	500 ml
Spray head	Standard
Colour	transparent
Labelling of hazardous substances	GHS02: Flame
Labelling of hazardous substances	GHS07 caution
Labelling of hazardous substances	GHS09 harmful to the environment
Version	Spray can
Type of product	Parting agent