



## High-temperature oil Ejector Lube, Contents: 500ml



### Order data

|              |               |
|--------------|---------------|
| Order number | 083097 500    |
| GTIN         | 5412386069505 |
| Item class   | 08E           |

### Description

#### Version:

Synthetic long-term lubricant, resistant to high temperatures.

Ideally suited to long-term lubrication of ejection pins, guide pins and precision mechanisms.

- **Fully synthetic lubricating oil, resistant to high temperatures up to 250°C.**
- **Reduced friction and wear.**
- **Resistant to high pressures, does not gum up.**
- **Leaves no residues on the moulded parts.**
- **Silicone-free.**
- **Non-flammable.**
- **Spray with spray valve that achieves practically 360° distribution – sprays even overhead.**

#### Application:

High-temperature lubricant for precision mechanisms. Long-term lubricant for ejection pins and guide pins on injection moulding machines. Presents baking on.

- **Apply a thin even film to the clean dry surface.**
- **Refer to the current safety data sheet (SDB) for safety instructions.**

### Technical description

|                                   |              |
|-----------------------------------|--------------|
| Operating temperature range       | -25 - 250 °C |
| Colour                            | transparent  |
| Labelling of hazardous substances | GHS02: Flame |
| Spray head                        | Standard     |
| Dynamic viscosity                 | 32 mPas      |
| hazardous goods class             | 2.1          |
| Solubility in water               | insoluble    |
| Contents                          | 0.5 l        |
| Version                           | Spray can    |
| Type of product                   | Lubricant    |