3M

Ear defenders, dependent on noise levels Peltor™ WS™ LiteCom PRO III, Type: PRO3



Order data

| Order number | 097799 PRO3 |
|--------------|---------------|
| GTIN | 7318640066960 |
| Item class | 04A |

Description

Version:

Noise-level-dependent high-performance hearing protection with integral analogue and digital radio intercom system. Two radio intercom systems (1 analogue / 1 digital) are pre-programmed ex-factory. 16 channels (analogue PMR) and 16 channels (digital PMR) are available as standard. The ear defenders can be programmed to up to 70 different radio channels. The Bluetooth[®] multipoint functionality permits seamless connection with mobile phones, so that you can make and receive and end phone calls without interrupting your work. The **noise-suppressing and watertight speech microphone** offers voice-triggered transmission (VOX) for free speech operation in noisy environments. The headset has a **rechargeable** lithium ion battery. SNR = 33 dB (H = 34 dB, M = 31 dB, L = 25 dB).

Combines hearing protection, headphones and microphone.

Application:

For communication in noisy demanding environments.

Standard:

EN 352-4; EN 352-6

Supplied with:

With battery, charger, extra hygiene kit and microphone protection. **Note:**

Hygiene sets are listed under No. 097767 size HY83

Technical description

| Working time | 11 h |
|-------------------------------|--|
| Weight | 490 g |
| Series | Peltor [™] WS [™] LiteCom [™] PRO III |
| SNR value (noise attenuation) | 33 dB(A) |
| Power supply | Rechargeable battery-powered |
| Standard | EN 352-4 |
| Standard | EN 352-6 |
| Type of product | Ear defenders |

Accessories

Hygiene kit Type HY83

097767 HY83