

GARANT Master Titan solid carbide mini milling cutter HPC, TiAlN, Ø e8 DC: 1mm



Order data

| Order number | 202287 1 | | |
|--------------|---------------|--|--|
| GTIN | 4062406270919 | | |
| Item class | 11Z | | |

Description

Version:

Extra short cutter for maximum stability. **Shank length to DIN** for improved support of the tool in the holder. This significantly increases the tool life.

Save the regrinding costs: It is cheaper to use a carbide mini slot drill to the limit of wear and throw it away, than to regrind it.

Attractively priced and extra stable version for high-power machining of titanium.

Technical description

| Helix angle | 40 degrees | | |
|---|----------------------------------|--|--|
| Direction of infeed | horizontal, oblique and vertical | | |
| Feed f_z for side milling in titanium > 850 N/mm ² | 0.005 mm | | |
| Flute length L _c | 2 mm | | |
| Cutting edge Ø D _c | 1 mm | | |
| No. of teeth Z | 2 | | |
| Shank | DIN 6535 HA to h6 | | |
| Tolerance nominal Ø | e8 | | |
| Overall length L | 44 mm | | |
| Shank Ø D _s | 4 mm | | |
| Corner rounding r _v | 0.02 mm | | |

| Series | Master Titan | | |
|--|-----------------------------|--|--|
| Coating | TiAlN | | |
| Tool material | Solid carbide | | |
| Standard | Manufacturer's standard | | |
| Туре | N | | |
| Cutting width a _e for milling operation | Full slot cutting depth 1×D | | |
| Cutting width a _e for milling operation | Full slot cutting depth 1×D | | |
| Through-coolant | no | | |
| Machining strategy | HPC | | |
| Colour ring | pink | | |
| Type of product | End / face mill | | |

User data

| | Suitability | \mathbf{V}_{c} | ISO code |
|----------------------------|-------------|------------------|----------|
| Ti > 850 N/mm ² | suitable | 60 m/min | S |
| wet maximum | suitable | | |