

**Garant**
**Solid carbide end torus cutter HPC, TiAlN, Ø h9 DC: 10mm**

**Order data**

Order number	206263 10
GTIN	4062406279899
Item class	11X

**Description**
**Version:**

Special centre cutting edge geometry for traverse milling at very high feed rates.

Tolerance: Corner radius  $R_1 = \pm 0.01$  mm.

**Application:**

**For copy and traverse milling** over the full range of hard machining **under HPC/HSC conditions**.

Using special milling strategies **very high rates of metal removal can be achieved**.

**Note:**

**Tools can be reground.**

With conically increasing recess to guarantee stability at long overhangs.

**Technical description**

No. of teeth Z	6
Shank Ø $D_s$	10 mm
Cutting edge Ø $D_c$	10 mm
Feed $f_z$ in steel < 900 N/mm <sup>2</sup>	0.14 mm
Overhang length $L_1$ incl. recess	48 mm
Setting angle $\kappa$	15 degrees
Overall length L	100 mm
Programming radius	2 mm
Dimension $a_{p\ max}$ transverse	0.7 mm

Flute length $L_c$	5.8 mm
maximum shank recess dia. $D_6$	9.9 mm
minimum shank recess dia. $D_5$	9 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	h9
Helix angle	15 degrees
Direction of infeed	horizontal and oblique
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Shank	DIN 6535 HA to h5
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End torus mill

## User data

	Suitability	$V_c$	ISO code
Steel < 500 N/mm <sup>2</sup>	suitable	170 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	150 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	135 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	130 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable	125 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable	95 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable	90 m/min	M
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		

dry	suitable only under restricted conditions
Air <b>Services</b>	suitable only under restricted conditions
Shank grinding Type HB	129100 HB