

### Abrasive fleece pad, 158×224 mm, Fleece structure: 400



#### **Order data**

| Order number | 555995 400    |
|--------------|---------------|
| GTIN         | 4062406300845 |
| Item class   | 51M           |

### **Description**

#### **Version:**

Synthetic nylon fleece impregnated with abrasive grit in synthetic resin bonding. High-performance fleece with **extremely dense grit distribution** deep into the fibres of the material. The special type of fleece structure permits **aggressive grinding characteristics**, a very long working life without clogging and an even **more uniform finish**.

### **Advantage:**

- · Adapts to the component shape.
- · The open structure prevents clogging and reduces heat development.
- · Even and reproducible finish.
- · Can be used wet or dry.
- · Contains no materials that could cause corrosion.

#### **Application:**

Can be used by hand, on hand block No. 556020 or on an orbital sander. **Fine / very fine:** for cleaning delicate surfaces, for removing light scratches on metals. Also suitable for applying fine / very fine matt finishes to steels and non-ferrous metals.

# **Technical description**

| Fleece structure | 400       |
|------------------|-----------|
| Grit equivalent  | 400 - 600 |
| Grit designation | fine      |
| Colour           | grey      |



| Version                                 | S Super Fine        |  |
|---|---------------------|--|
| Iron, sulphur and chlorine constituents | < 0.1 %             |  |
| Width                                   | 158 mm              |  |
| Length                                  | 224 mm              |  |
| Product name attribute                  | 158×224 mm          |  |
| Type of product                         | Abrasive fleece pad |  |

# **User data**

|                                | Suitability                               | $\mathbf{V}_{c}$ | ISO code |
|--------------------------------|---|------------------|----------|
| Alu Mg                         | suitable                                  |                  |          |
| Steel < 900 N/mm <sup>2</sup>  | suitable                                  |                  |          |
| Steel < 1400 N/mm <sup>2</sup> | suitable                                  |                  |          |
| Steel < 55 HRC                 | suitable                                  |                  |          |
| Steel < 60 HRC                 | suitable                                  |                  |          |
| Steel < 67 HRC                 | suitable                                  |                  |          |
| INOX                           | suitable                                  |                  |          |
| Ti                             | suitable                                  |                  |          |
| GG(G)                          | suitable                                  |                  |          |
| CuZn                           | suitable                                  |                  |          |
| Plastic, GRP                   | suitable                                  |                  |          |
| Wood                           | suitable                                  |                  |          |
| Stone                          | suitable only under restricted conditions |                  |          |
| Paint                          | suitable                                  |                  |          |
| Uni                            | suitable                                  |                  |          |
| wet maximum                    | suitable only under restricted conditions |                  |          |
| dry                            | suitable                                  |                  |          |

# **Accessories**

| Hand block | 556020 |
|------------|--------|
| Mandrel    | 556030 |