

## Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC h7: 3,3mm



## **Order data**

Order number	123101 3,3
GTIN	4045197448835
Item class	11E

### **Description**

#### **Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.** 

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

**Convex cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

#### **Advantage:**

High process reliability and surface quality of the hole.

### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form **HB** and **HE** supplied at the same price as HA.

Form **HB:** order with **No. 123102**.

Form **HE**: order with **No. 123101 + 129100 HE**.

**NEW GENERATION AVAILABLE!** 

Recommended successor products are No. 123025 and 123035.

## **Technical description**

Number of cutting edges Z	2	
Feed f in steel < 1100 N/mm <sup>2</sup>	0.1 mm/rev.	
Shank tolerance	h6	
Flute length L <sub>c</sub>	34 mm	
Nominal Ø D <sub>C</sub>	3.3 mm	
Tolerance nominal Ø	h7	

Shank Ø D <sub>s</sub>	6 mm		
Overall length L	72 mm		
Standard	Manufacturer's standard		
recommended maximum drilling depth $L_2$	29.1 mm		
Coating	TiAlN		
Tool material	Solid carbide		
Version	8×D		
Point angle	135 degrees		
Shank	DIN 6535 HA to h6		
Through-coolant	yes, with 25 bar		
Machining strategy	HPC		
Semi-Standard	yes		
Colour ring	green		
Type of product	Jobber drill		

# **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	180 m/min	N
Alu > 10% Si	suitable only under restricted conditions	140 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable only under restricted conditions	110 m/min	Р
Steel < 750 N/mm <sup>2</sup>	suitable	90 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	80 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	50 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	35 m/min	Р
INOX < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	40 m/min	М

INOX > 900 N/mm <sup>2</sup>	suitable only under restricted conditions	35 m/min	М
GG(G)	suitable	70 m/min	K
Uni	suitable		
wet maximum Services	suitable		

Shank grinding Type HE

129100 HE