## Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC h7: 6,8mm



### Order data

Order number	123101 6,8		
GTIN	4045197451712		
Item class	11E		

## Description

#### Version:

Cutting chisel edge with high centring accuracy due to strong core and special point geometry.

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

**Convex cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

#### Advantage:

High process reliability and surface quality of the hole. Note: Flute length  $L_c = L_2 + 1.5 \times D_c$ . Form HB and HE supplied at the same price as HA. Form HB: order with No. 123102. Form HE: order with No. 123101 + 129100 HE. NEW GENERATION AVAILABLE! Recommended successor products are No. 123025 and 123035.

## **Technical description**

Number of cutting edges Z	2		
Feed f in steel < 1100 N/mm <sup>2</sup>	0.15 mm/rev.		
Flute length $L_c$	76 mm		
Shank tolerance	h6		
Nominal Ø D <sub>c</sub>	6.8 mm		
Tolerance nominal Ø	h7		

© Hoffmann GmbH Qualitätswerkzeuge

Shank Ø D <sub>s</sub>	8 mm		
Overall length L	114 mm		
Standard	Manufacturer's standard		
recommended maximum drilling depth $L_2$	65.8 mm		
Coating	TiAIN		
Tool material	Solid carbide		
Version	8×D		
Point angle	135 degrees		
Shank	DIN 6535 HA to h6		
Through-coolant	yes, with 25 bar		
Machining strategy	HPC		
Semi-Standard	yes		
Colour ring	green		
Type of product	Jobber drill		

# User data

	Suitability	V <sub>c</sub>	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	180 m/min	Ν
Alu > 10% Si	suitable only under restricted conditions	140 m/min	Ν
Steel < 500 N/mm <sup>2</sup>	suitable only under restricted conditions	110 m/min	Р
Steel < 750 N/mm²	suitable	90 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	80 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	50 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	35 m/min	Р
INOX < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	40 m/min	М

INOX > 900 N/mm <sup>2</sup>	suitable only under restricted conditions	35 m/min	М
GG(G)	suitable	70 m/min	К
Uni	suitable		
<del>wet maximum</del> Services	suitable		

Shank grinding Type HE

129100 HE