

Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC h7: 4,6mm



Order data

Order number	123101 4,6
GTIN	4045197451545
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.**

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

Convex cutting edges with honed edges and special flute profile for **short chips**, even on long chipping materials.

Advantage:

High process reliability and surface quality of the hole.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form **HB** and **HE** supplied at the same price as HA.

Form **HB:** order with **No. 123102**.

Form **HE**: order with **No. 123101 + 129100 HE**.

NEW GENERATION AVAILABLE!

Recommended successor products are No. 123025 and 123035.

Technical description

Feed f in steel < 1100 N/mm ²	0.1 mm/rev.	
Number of cutting edges Z	2	
Flute length L _c	43 mm	
Shank tolerance	h6	
Nominal Ø D _c	4.6 mm	
Tolerance nominal Ø	h7	



Shank Ø D _s	6 mm		
Overall length L	81 mm		
Standard	Manufacturer's standard		
recommended maximum drilling depth L_2	36.1 mm		
Coating	TiAIN		
Tool material	Solid carbide		
Version	8×D		
Point angle	135 degrees		
Shank	DIN 6535 HA to h6		
Through-coolant	yes, with 25 bar		
Machining strategy	HPC		
Semi-Standard	yes		
Colour ring	green		
Type of product	Jobber drill		

User data

	Suitability	\mathbf{V}_{c}	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	180 m/min	N
Alu > 10% Si	suitable only under restricted conditions	140 m/min	N
Steel < 500 N/mm ²	suitable only under restricted conditions	110 m/min	Р
Steel < 750 N/mm ²	suitable	90 m/min	Р
Steel < 900 N/mm ²	suitable	80 m/min	Р
Steel < 1100 N/mm ²	suitable	50 m/min	Р
Steel < 1400 N/mm ²	suitable	35 m/min	Р
INOX < 900 N/mm ²	suitable only under restricted conditions	40 m/min	М

INOX > 900 N/mm ²	suitable only under restricted conditions	35 m/min	М
GG(G)	suitable	70 m/min	K
Uni	suitable		
wet maximum Services	suitable		

Shank grinding Type HE

129100 HE