



## Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø h7: 7,4 mm



### Order data

Order number	123102 7,4
GTIN	4045197458537
Item class	11E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

Particularly high alignment accuracy due to **4 guide chamfers** which stabilise the drill even at extreme depths!

**Convex cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

#### Advantage:

**High process reliability and surface quality of the hole.**

#### Recommendation:

##### Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

#### Note:

**NEW GENERATION AVAILABLE!**

**Recommended successor products are No. 123026 and 123036.**

Machining strategy: HPC

Norm: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

Flute length: 76 mm

Overall length  $L_{tot}$ : 114 mm

Shank Ø: 8 mm

Feed  $f$  in steel < 1100 N/mm<sup>2</sup>: 0.15 mm/rev.

### Technical description

Feed $f$ in steel < 1100 N/mm <sup>2</sup>	0.15 mm/rev.
--	--------------

Nominal Ø	7.4 mm
Number of cutting edges Z	2
Flute length	76 mm
Shank tolerance	h6
Tolerance nominal Ø	h7
Shank Ø	8 mm
Overall length L <sub>tot</sub>	114 mm
Norm	Manufacturer's standard
recommended maximum drilling depth	64.9 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	135 degrees
Schaft	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green