ÅGarant^{*}

NC reamer H7, uncoated, Nominal Ø: 10,01 mm

Order data	
Order number	162900 10,01
GTIN	4045197090881
Item class	110

Description

Version:

Version suitable for NC similar to DIN 212 with straight shank Ø for standard chucking especially in hydraulic chucks or high precision collet chucks. For highest concentricity and process reliability. No need to order special collets.

With long flutes and left-hand helix.

 $\leq \emptyset$ size 1.7 with 3 teeth; $\geq \emptyset$ size 1.8 even number of teeth and irregular spacing. $\leq \emptyset$ size 3.7 both ends with centre points; $\geq \emptyset$ size 3.8 both ends with centre holes.

Reamer manufacturing tolerance to DIN 1420 for H7 hole tolerance.

Note:

For reamers in 1/100 sizes see No. 162902. For reamers with diameters and fits to specification see No. 162951 Tool material: HSS E Norm: Manufacturer's standard Through-coolant: false Skaft: DIN 1835 A to h6 Application for type of drilling: for through holes Tolerance: 0 / 0,005Number of cutting edges Z: 6 Tolerance: 0 / 0,005Overhang L_A: 91 mm Overall length L_{tot}: 133 mm Number of cutting edges Z: 6 Shank Ø: 10 mm Feed f in steel < 750 N/mm²: 0.15 mm/rev.

Technical description

Skaft	DIN 1835 A to h6
Machining strategy	

© Hoffmann GmbH Qualitätswerkzeuge

Norm	Manufacturer's standard
Туре	
Through-coolant	no
Tool material	HSS E
Colour ring	green
Application for type of drilling	for through holes
Coating	uncoated
Helix angle	degrees
Use for drilling	
Type of product	