## Re-Bo

Metal circular saw blade fine, uncoated, Ø×thickness: 80X0,5mm



### **Order data**

| Order number | 175000 80X0,5 |  |  |
|--------------|---------------|--|--|
| GTIN         | 4045197242969 |  |  |
| Item class   | 17A           |  |  |

## Description

#### Version:

**DIN 1837 A fine-toothed** with raked teeth form A. Straight teeth with relatively small indentations.

All blades are hollow ground to give side clearance. All sizes with 200 mm Ø and very thin blades have a bore collar for stabilisation. Accuracy, tooth form, and side clearance grinding according to DIN 1840.

#### Application:

For thin-walled components and small cutting depths.

#### Note:

The concentricity and axial run-out values are considerably better than the figures according to DIN 1840, in some cases by up to 50 %.

## **Technical description**

| Ø         | 80 mm  |
|-----------|--------|
| Thickness | 0.5 mm |
| Bore Ø    | 22 mm  |

| No. of teeth Z  | 128                |  |  |
|-----------------|--------------------|--|--|
| Coating         | uncoated           |  |  |
| Tool material   | HSS                |  |  |
| Standard        | DIN 1837           |  |  |
| Through-coolant | no                 |  |  |
| Type of product | Circular saw blade |  |  |

# User data

|                               | Suitability                               | V <sub>c</sub> | ISO code |
|-------------------------------|---|----------------|----------|
| Steel < 500 N/mm <sup>2</sup> | suitable                                  | 37 m/min       | Р        |
| Steel < 750 N/mm <sup>2</sup> | suitable                                  | 22 m/min       | Р        |
| Steel < 900 N/mm <sup>2</sup> | suitable                                  | 20 m/min       | Р        |
| Steel < 1100 N/mm²            | suitable only under restricted conditions | 15 m/min       | Р        |
| INOX < 900 N/mm <sup>2</sup>  | suitable only under restricted conditions | 11 m/min       | М        |
| INOX > 900 N/mm <sup>2</sup>  | suitable only under restricted conditions | 11 m/min       | М        |
| GG(G)                         | suitable                                  | 27 m/min       | К        |
| CuZn                          | suitable                                  | 400 m/min      | Ν        |
| Uni                           | suitable                                  |                |          |
| wet maximum                   | suitable                                  |                |          |
| dry                           | suitable only under restricted conditions |                |          |
| Air                           | suitable only under restricted conditions |                |          |