

Garant

Solid carbide milling cutter Composite, compacting cut, Diamond, Ø h10 DC: 5mm



Order data

Order number	209548 5
GTIN	4062406362386
Item class	100

Description

Version:

Specifically **developed Tool cutting edge has been specifically developed further** for optimum machining of composite materials.
Length similar to **DIN 6527 long**.
Left-hand helix, **compacting cut**. The material is pushed down on to the substrate. Highly suitable for thin materials.

Technical description

Helix angle	8 degrees
Overhang length L_1 incl. recess	19 mm
Cutting edge $\varnothing D_c$	5 mm
Flute length L_c	13 mm
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	h10
Corner chamfer width at 45°	0.1 mm
Overall length L	57 mm
Recess $\varnothing D_1$	4.9 mm
Feed f_z for slot milling in GRP CRP	0.021 mm
No. of teeth Z	8
Corner chamfer angle	45 degrees

Shank $\varnothing D_s$	6 mm
Direction of infeed	horizontal, oblique and vertical
Coating	Diamond
Tool material	Solid carbide
Standard	DIN 6527
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	black
Type of product	End / face mill

User data

	Suitability	V_c	ISO code
PVDF GF20	suitable	100 m/min	N
POM GF25	suitable	100 m/min	N
PA 66 GF30	suitable	100 m/min	N
PEEK GF30	suitable	100 m/min	N
PTFE CF25	suitable	100 m/min	N
PEEK CF30	suitable	100 m/min	N
Hybrids	suitable		
Honeycomb sandwich	suitable	195 m/min	N
CRP	suitable	145 m/min	N
GRP, CRP	suitable	145 m/min	N
Graphite	suitable	200 m/min	N
wet maximum	suitable		
dry	suitable		
Air	suitable		