

# Solid carbide HPC deep hole drill plain shank DIN 6535 HA 30×D, DLC, $\varnothing$ DC h7: 4,2mm

Ord	er	da	ata
-----	----	----	-----

Order number	123595 4,2
GTIN	4045197354952
Item class	11E

### **Description**

#### **Version:**

Spiral fluted, with **6 guide chamfers** and internal cooling channels. New generation of high performance deep hole drills in the HPC range. **With 135° point angle** and special **h7 cutting edge tolerance** for optimum generation of a deep hole. **High roundness and alignment accuracy of the deep hole.** 

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the  $16\times D$  deep hole drill, an initial centre drilling with No. 121068 - 121121 or  $4\times D$  pilot drilling operation with pilot drill No. 122606 is necessary. For deep holes greater than  $20\times D$ , a pilot hole to the maximum drilling depth with pilot drill No. 122606 is absolutely essential.

The generation of a pilot hole improves process reliability. See also pages 140/141.

## **Technical description**

Flute length L <sub>c</sub>	135 mm	
Feed f in aluminium short-chipping	0.19 mm/rev.	
Nominal Ø D <sub>c</sub>	4.2 mm	
Number of cutting edges Z	2	
Tolerance nominal Ø	h7	
Shank Ø D <sub>s</sub>	6 mm	
Overall length L	185 mm	
Standard	Manufacturer's standard	

recommended maximum drilling depth $L_2$	128.7 mm	
Coating	DLC	
Tool material	Solid carbide	
Version	30×D	
Point angle	135 degrees	
Shank	DIN 6535 HA to h6	
Through-coolant	yes, with 40 bar	
Machining strategy	HPC	
Pilot drill required	yes, pilot drill	
Colour ring	yellow	
Type of product	Jobber drill	

## **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Aluminium	suitable	120 m/min	N
Aluminium (short chipping)	suitable	150 m/min	N
Alu > 10% Si	suitable	110 m/min	N
PMMA acrylic	suitable	120 m/min	N
PEEK	suitable	95 m/min	N
PVDF GF20	suitable	70 m/min	N
PA 66 GF30	suitable	65 m/min	N
PEEK GF30	suitable	55 m/min	N
PTFE CF25	suitable	65 m/min	N
Cu	suitable	70 m/min	N
CuZn	suitable	80 m/min	N
GRP	suitable	65 m/min	N
CRP	suitable	65 m/min	N
wet maximum	suitable		

wet minimum Services	<del>suitable</del>	
Shank grinding Type HB		129100 HB
Shank grinding Type HE		129100 HE