KOMET

KUB Pentron[®] indexable drill Plain shank, 2×D, Ø Dc: 37,5mm



Order data

Order number	236614 37,5
GTIN	4047109277694
Item class	24P

Description

Version:

Bore tolerance: $\varnothing D - 0.1 / + 0.2$

- Very high performance and long tool life thanks to optimised base body strength and special surface treatment.
- · Best dimensional accuracy under very difficult drilling conditions.
- · Stock costs reduced because internal and external inserts are identical.
- Offset-axis drilling is possible up to $V_{max} = 0.25$ mm. Maximum $\emptyset = D + 0.5$ mm achievable by offsetting.

Application:

· Under extreme machining conditions.

With indexable inserts No. 236605 – 236610.

Supplied with:

Clamp screws (without indexable inserts).

Note:

Version $2 \times D$ and $3 \times D$ with ABS^{*} also available on request in imperial sizes. Version with PSC shank available on request.

Technical description

ISO code indexable insert	SOGX 120408 42
Shank Ø D _s	40 mm
Shank length L _s	68 mm
Pack of insert screws	239652 20IP (6.3 Nm)
Reach L ₁	76 mm

Number of cutting edges Z	1
Series	KUB Pentron®
Nominal Ø D	37.5
Overhang L _A	103 mm
Drill depth for indexable insert drill up to	2×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC
Type of product	Indexable drill

Accessories

PrecisionBit for Torx Plus [®] , 1/4 inch E 6.3 Torx Plus [®] profile 20IP	674252 20IP
Torx Plus [®] insert screw set10 pieces Drive 20IP	239652 20IP
8 mm blade with magnetwith 1/4 inch bit holder overall length 50 mm	659874 50
Torque screwdriverwith scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
Torque screwdriverwith scale, to take interchangeable blades maximum torque 1600 cNm	659957 1600